

## 55-C0210/D

**CONTROLS**



55-C0210/D Basic model

### General description

This universal saw, completed with the suitable accessories, can be used to cut concrete and rock cores, and irregular rock samples in order to obtain geometrically defined specimens. It can be fit with 300 to 450 mm dia. blades.

The head is adjustable in height. The tilting motor head permit cuts up to 45° inclination. The tank and the trolley are zinc plated to avoid corrosion. Complete with safety device which prevents the restarts of the machine after unexpected interruption, water pump for cooling the blade and double filtering system.

Cutting blade and accessories to cut cores, rock and other building materials, not included. See accessories.

Safety devices conforming to CE prescriptions.

**Specifications**

- Max. cutting height: 115 mm with 350 mm dia. blade and 165 mm with 450 mm dia. blade
- Max. blade diameter: 450 mm, hole 25.4 mm dia.
- Power: 3 kW
- Overall dimensions (lxdxh): 1300x700x1300 mm
- Weight approx.: 92 kg



55-C0210/D complete with 55-C0210/5 V-shaped support for cylinders and cores up to 160 mm dia. and diamond blade 55-C0210/1.



55-C0210/D complete with 45-C0210/6 locking clamp device for irregular pieces and diamond blade 55-C0210/1.

**Ordering information**

Code	Description
<b>55-C0210/D</b>	Concrete, rock and masonry saw. 380V, 50 Hz, 3 ph
<b>55-C0210/DZ</b>	Concrete, rock and masonry saw. 220V, 60 Hz, 3 ph

**Accessories**

Code	Description
<b>45-C0211/4</b>	Diamond blade, 350 mm dia., for hard rock
<b>55-C0211/1</b>	Diamond blade, 350 mm dia., for concrete
<b>55-C0210/1</b>	Diamond blade, 450 mm dia., for concrete
<b>55-C0210/5</b>	V-shaped support for cylinders and cores up to 160 mm dia. Weight approx.: 4 kg
<b>45-C0210/6</b>	Locking clamp device for irregular pieces.



wfi.co.uk

CONTROLS S.R.L. is certified to ISO 9001:2008

**controlsgroup.net**

Italy  
controlsitalia.it

France  
controls.fr

Mexico  
controls.com.mx

Poland  
controls.pl

Spain  
controls.es

United Kingdom  
controlstesting.co.uk